

## DECLARATION OF PERFORMANCE

Nr BZS/028

1. Identification code of the product-type: **sklejka trudno zapalna wodoodporna foliowana filmem fenolowym grubość  $\geq 12$  mm (plywood low flammability, coated phenol film, thickness  $\geq 12$  mm)**
2. Serial number: -
3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **as a structural element, according to EN 636-3, for floorings**



4. Name, registered trade mark and contact address of the manufacturer: **Zakłady Sklejek „Sklejka-Multi” S.A. 85-752 Bydgoszcz, ul. Fordońska 154**
5. Where applicable, name and contact address of the authorised representative: -
6. System of assessment and verification of constancy of performance of the construction product: **2+**  
 Name and identification number of the notified body:  
**MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 - CPR**  
 has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.  
 Certificate of factory production control in accordance of conformity system 2+  
**0763 – CPR - 6061**
8. Declared performance

| Essential characteristics          | Performance   | Harmonised technical specification |
|------------------------------------|---|------------------------------------|
| Bending strength                   | F 35 / F 25   | EN 13986:2004+A1:2015              |
| Modulus of elasticity              | E 80 / E 40   |                                    |
| Bonding quality                    | Class 3   |                                    |
| Class hygiene                      | E1  |                                    |
| Reaction to fire class             | B <sub>fl</sub> -s1<br>this classification is valid for the following end use conditions: standard non-combustible substrate according EN 13238:2011, fibre cement board with thickness (8 +/- 2) mm, with density (1800 +/- 200) kg/m <sup>3</sup> and with classification A2 <sub>fl</sub> -s1 – without attachment (e.g. adhesive) |                                    |
| Water vapour permeability $\mu$    | wet 90 / dry 220  |                                    |
| Content of pentachlorophenol (PCP) | Does not contain  |                                    |
| Airborne sound insulation          | NPD   |                                    |
| Sound absorption $\alpha$          | 0,10 / 0,30   |                                    |
| Thermal conductivity $\lambda$     | 0,17  |                                    |
| Biological durability              | Class 3 (coated and edge sealed)  |                                    |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Pełnomocnik ds. SZJ

Wojciech Krasicki



Bydgoszcz 01.11.2020.