

DECLARATION OF PERFORMANCE

Nr BZS/031

1. Identification code of the product-type: **sklejka bukowa trudno zapalna gr. min. 6 mmmm (flame retardant beech plywood thickness min. 6 mm)**
2. Serial number: -
3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **as a structural component for floorings, for use in humid conditions according to PN-EN 636-2**



4. Name, registered trade mark and contact address of the manufacturer: **Sklejek „Sklejka-Multi” S.A. 85-752 Bydgoszcz , ul. Fordońska 154**
5. Where applicable, name and contact address of the authorised representative: -
6. System of assessment and verification of constancy of performance of the construction product: **1**
 Name and identification number of the notified body:

MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 - CPR

issued the Certificate of Constancy of Performance No. **0763-CPR-6063**, which confirms that all provisions regarding the assessment and verification of constancy of performance and performance, as set out in Annex ZA of the harmonized standard **EN 13986: 2004 + A1: 2015** in system **1** with regard to properties performance specified in the certificate are applied and that the product meets all the requirements specified for these performance properties.

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Bending strength	F35 / F25	EN 13986:2004+A1:2015
Modulus of elasticity	E80 / E40	
Bonding quality	Class 3	
Release of formaldehyde	E1	
Reaction to fire class	B _f -s1 This classification is valid for the following applications: material laid in systems with ventilated or non-ventilated air cavity, laid and / or fixed directly or via joists to mineral substrates of class A1 or A2-s1, d0	
Water vapour permeability μ	wet 90 / dry 220	
Content of pentachlorophenol (PCP)	Does not contain	
Airborne sound insulation	NPD	
Sound absorption α	0,10 / 0,30	
Thermal conductivity λ	0,17	
Biological durability	Class 2	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Pełnomocnik ds. SZJ

Wojciech Krasicki



Bydgoszcz 01.06.2023.