

DECLARATION OF PERFORMANCE

Nr BZS/032

1. Identification code of the product-type: **sklejka sosnowa, trudno zapalna grubość \geq 12 mm (flame retardant pine plywood thickness \geq 12 mm)**
2. Serial number: -
3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **as a structural component for walls and roofs, for use in humid conditions according to PN-EN 636-2**



4. Name, registered trade mark and contact address of the manufacturer: **Zakłady Sklejek „Sklejka-Multi” S.A. 85-752 Bydgoszcz , ul. Fordońska 154**

5. Where applicable, name and contact address of the authorised representative: -

6. System of assessment and verification of constancy of performance of the construction product: **1**

Name and identification number of the notified body:

MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 - CPR

issued the Certificate of Constancy of Performance No. **0763-CPR-6064** according to **AVCP system 1**, which confirms that all provisions regarding the assessment and verification of constancy of performance and performance, as set out in Annex ZA of the harmonized standard **EN 13986: 2004 + A1: 2015**, with regard to properties performance specified in the certificate are applied and that the product meets all the requirements specified for these performance properties.

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Bending strength	F25 / F20	EN 13986:2004+A1:2015
Modulus of elasticity	E50 / E35	
Bonding quality	Class 3	
Release of formaldehyde	E1	
Reaction to fire class	B-s1, d0 This classification is valid for the following end use conditions: mechanically fastened to wooden slats, with vertical and/or horizontal joints, ventilated or un ventilated air gap	
Water vapour permeability μ	wet 90 / dry 220	
Content of pentachlorophenol (PCP)	Does not contain	
Airborne sound insulation	NPD	
Sound absorption α	0,10 / 0,30	
Thermal conductivity λ	0,17	
Biological durability	Class 2	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Pełnomocnik ds. SZJ

Wojciech Krasicki



Bydgoszcz 01.06.2023.