

DECLARATION OF PERFORMANCE

Nr BZS/002

- Identification code of the product-type: **sklejka ogólnego przeznaczenia wodoodporna iglasta grubość 9 - 50 mm (waterproof plywood from softwood thickness 9 - 50 mm)**
- Serial number: -
- Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **as a structural element, with unprotected surface humid conditions according to EN 636-2, with a protected surface exterior conditions according to EN 636-3**
- Name, registered trade mark and contact address of the manufacturer: **Bydgoskie Zakłady Sklejek „Sklejka-Multi” S.A. 85-752 Bydgoszcz , ul. Fordońska 154**
- Where applicable, name and contact address of the authorised representative: -
- System of assessment and verification of constancy of performance of the construction product: **2+**
Name and identification number of the notified body:
MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 - CPR
has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.
Certificate of factory production control in accordance of conformity system 2+
0763 – CPR - 6162
- Declared performance

| Performance characteristic | Declared performance properties | | Harmonized technical specification |
|---|---------------------------------------|----------------|------------------------------------|
| Bending strength f_m II | 45 N/mm2 | | EN 13986:2004+A1:2015 |
| Bending strength f_m \perp | 38 N/mm ² | | |
| Modulus of Elasticity E_m II | 5400 N/mm2 | | |
| Modulus of Elasticity E_m \perp | 3600 N/mm2 | | |
| Bonding quality | Class 3 | | |
| Release of formaldehyde | E1 | | |
| Reaction to fire | D-s2, d0 | | |
| Water vapour permeability | Wet cup μ 90 Dry cup μ 220 | | |
| Airborn sound insulation | NPD | | |
| Sound absorption | 250 – 500 Hz | 1000 – 2000 Hz | |
| | 0,10 | 0,30 | |
| Thermal conductivity λ (W/(mK)) | 0,17 | | |
| Strength and stiffness for structural use | NPD | | |
| Mechanical durability | NPD | | |
| Biological durability | Class 2 | | |
| Content of pentachlorophenol | Does not contain | | |
| Racking resistance | NPD | | |
| Embedment strength | NPD | | |



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technolog jakości

Wojciech Krasicki

TECHNOLOG JAKOŚCI

Wojciech Krasicki

Bydgoszcz 01.07.2025.