## **DECLARATION OF PERFORMANCE**

## Nr BZS/010

- 1. Identification code of the product-type: sklejka foliowana wodoodporna grubość 9 50 mm (waterproof coated plywood thickness 9 50 mm)
- 2. Serial number: -
- Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: as a structural element, exterior conditions according to EN 636-3
- 4. Name, registered trade mark and contact address of the manufacturer: Bydgoskie Zakłady Sklejek "Sklejka-Multi" S.A. 85-752 Bydgoszcz , ul. Fordońska 154
- 5. Where applicable, name and contact address of the authorised representative: -
- 6. System of assessment and verification of constancy of performance of the construction product: **2+** Name and identification number of the notified body:

## MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 - CPR

has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

Certificate of factory production control in accordance of conformity system 2+

## 0763 - CPR - 6162

8. Declared performance

Performance characteristic	Declared performance properties		Harmonized
			technical
			specification
Bending strength f <sub>m</sub> II	45 N/mm2		
Bending strength f <sub>m</sub> $\perp$	38 N/mm <sup>2</sup>		
Modulus of Elasticy Em II	5400 N/mm2		
Modulus of Elasticy Em 丄	3600 N/mm2		
Bonding quality	Class 3		
Release of formaldehyde	E1		
Reaction to fire	D-s2,d0		15
Water vapour permeability	Wet cup μ 90 Dry cup μ 220		13986:2004+A1:2015
Airborn sound insulation	NPD		44
Sound absorption	250 – 500 Hz	1000 – 2000 Hz	:500
	0,10	0,30	986
Thermal conductivity λ (W/(mK))	0,17		133
Strengthand stiffness for structural use	NPD		Z
Mechanical durability	NPD		
Bilogical durability	Class 3 (coated and edge sealed)		
Content of pentachlorophenol	Does not contain		
Racking resistance	NPD		
Embedment strength	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technolog jakości

Wojciech Krasicki

TECHNOLOG JAKOŚCI MIQSI (W.) Wojciech Krasicki

Bydgoszcz 01.07.2025.