

DECLARATION OF PERFORMANCE

Nr BZS/028

- Identification code of the product-type: **sklejka trudno zapalna foliowana filmem fenolowym grubość ≥ 12 mm (flame retardant plywood, coated phenol film, thickness ≥ 12 mm)**
- Serial number: -
- Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **as a structural element, exterior conditions according to EN 636-3, for floorings**
- Name, registered trade mark and contact address of the manufacturer: **Bydgoskie Zakłady Sklejek „Sklejka-Multi” S.A. 85-752 Bydgoszcz, ul. Fordońska 154**
- Where applicable, name and contact address of the authorised representative: -
- System of assessment and verification of constancy of performance of the construction product: **2+**
Name and identification number of the notified body:
MPA Eberswalde Materialprüfanstalt Brandenburg GmbH Alfred-Möller-Straße 1 16225 Eberswalde 0763 – CPR has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.
Certificate of factory production control in accordance of conformity system 2+ **0763 – CPR - 6161**
- Declared performance

Performance characteristic	Declared performance properties		Harmonized technical specification
Bending strength f_m II	45 N/mm2		EN 13986:2004+A1:2015
Bending strength f_m \perp	38 N/mm ²		
Modulus of Elasticity E_m II	6300 N/mm2		
Modulus of Elasticity E_m \perp	4500 N/mm2		
Bonding quality	Class 3		
Release of formaldehyde	E1		
Reaction to fire	Bfl-s1 this classification is valid for the following end use conditions: standard non-combustible substrate according EN 13238:2011, fibre cement board with thickness (8 +/- 2) mm, with density (1800 +/- 200) kg/m3 and with classification A2fl-s1 – without attachment (e.g. adhesive)		
Water vapour permeability	Wet cup μ 90 Dry cup μ 220		
Airborn sound insulation	NPD		
Sound absorption	250 – 500 Hz	1000 – 2000 Hz	
	0,10	0,30	
Thermal conductivity λ (W/(mK))	0,17		
Strength and stiffness for structural use	NPD		
Mechanical durability	NPD		
Biological durability	Class 3 (coated and edge sealed)		
Content of pentachlorophenol	Does not contain		
Racking resistance	NPD		
Embedment strength	NPD		



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technolog jakości

Wojciech Krasicki

TECHNOLOG JAKOŚCI
Wojciech Krasicki
Wojciech Krasicki

Bydgoszcz 01.07.2025.